




NAME: LED Canopy Light

P/N: SS-CU-130W

Advantage:

- UL cUL CE RoHS certificate
- PHILIPS Chip, high CRI
- Mean Well IP65 driver, input voltage 100-277VAC
- No UV or IR in the beam
- Easy to install and operate
- Energy saving, long lifespan
- Light is soft and uniform, safe to eyes
- Instant start, NO flickering, NO humming
- Green and eco-friendly without mercury.



Application:

- ◆ Gas station

Product Specifications

Product name	LED Canopy Light
Part No	SS-CU-130W
Light Type	Canopy Light
Dimension	380*380*72mm

Technical Characteristic

Color temperature	2700-7000K
CRI	>80
Lumen	11500-14500LM
Input Power	130W
Viewing Angle	100 Degree
Input Voltage	AC100-277V 50/60Hz
Driver model	CLG-150-48A(Mean Well Driver)
PFC	>0.9
Waterproof Rating	IP65

Materials


LED Brand	PHILIPS
LED Type	3030, 1.5W
LED QTY	140 PCS
Housing	Aluminum
Housing color	White

Others


Operating Temperature	-20°C TO 45°C
Operating Humidity	20%-90% RH
Storage Temperature	-30°C TO 80°C
Storage Humidity	10%-95%
Application	Outdoor
Safety Certification	UL、cUL
Warranty	5 Years

Light Distribution Testing Parameters

DATA OF LAMP		PHOTOMETRIC DATA Eff: 106.47 lm/W			
MODEL	SS-CANOPY-130W-U	I _{max} (cd)	5701	S/MH (C0/180)	1.27
NOMINAL POWER (W)	130	LOR (%)	100.0	S/MH (C90/270)	1.27
RATED VOLTAGE (V)	277	TOTAL FLUX (lm)	13748	η UP, DN (C0-180)	0.0, 50.2
NOMINAL FLUX (lm)	13748.3	CIE CLASS	DIRECT	η UP, DN (C180-360)	0.1, 49.7
LAMPS INSIDE	1	η up (%)	0.1	CIBSE SHR NOM	1.25
TEST VOLTAGE (V)	277.0	η down (%)	99.9	CIBSE SHR MAX	1.35



Flux out: 10587 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

Package

Lamps Net Weight: 6.3 Kg/pcs

	Size	Qty/Carton	Weight/Carton
Outer box	400*400*120mm	1	7.3 kg



Notice for User

- ◆ Please turn off power before install or change assembly parts.
- ◆ The input voltage and lamps should be matched, after connecting the power line, Please make sure the wiring section is insulated.
- ◆ No-professionals, must not install and disassemble the lamps.

Trouble Shootings

Troubles	Check points
Flickering of the light	Turn off the power and turn on again in 3 minutes. If same phenomena occur, then call agencies
Out of working	Please check the connection